

# Montana Department of Transportation Bridge Bureau Approved Construction Equipment List

lake:	Diamond Products				
lodel:	TBG134				
quipment Type:	Bridge Deck Groover				
Contractor Modifications:	None				
Interstate Approval Conditions			Non-Interstate Approval Conditions		
Approval Type	Crossing and Operating	Аррг	oval Type	Crossing and Operating	
Speed:	No Restriction	Spee	ed:	No Restriction	
Weight:	12,500 lb or less	Weig	ıht:	12,500 lb or less	
Traffic:	Approved with Regular Traffic	Traff	ic:	Approved with Regular Traffic	
Location Restrictions:	No Restriction	Loca Rest	tion rictions:	No Restriction	
Comments:		-			
same time this equipment is on the	and specifications on following pages. Approval does not be bridge.				

## **TBG134 Bridge Deck Groover**

### **FEATURES:**

- · Removable seat and flip up operators platform
- · Night operation light package
- · Safety strobe lights
- · Adjustable carriage travel limit switches
- · Lift eyes
- 90 gallon fuel capacity allows for up to 10 hours of operation
- Power steering
- · Rear crab steer allows for operation in small areas
- Grooves within 12" (34.48cm) of curb or barrier wall

#### Specifications:

**Engine:** Caterpillar C4.4 174HP (129.7Kw) @ 2200rpm turbocharged/intercooled electronically controlled diesel engine. Meets U.S. EPA Tier 4 Final and EU stage IV emission requirements. Fuel consumption is approximately 9gph (34 LPH)

Fuel Capacity: 90 gallon (370L) diesel fuel Tank Capacity: 70 gallon (259L) hydraulic oil

Dimensions: Length 8ft (2.44 meters), Width 8ft, 2in (2.47 meters), Height 10ft (3.04 meters), Weight 12,500lbs

(26,400kg)

Cutting Width: 39in (99.06cm)
Blade Diameter: 12in (30.48cm)

Part #: TBG134, Catalog #: 90172

See page 2 for picture w/ dimensions.


### **UNIQUE "CRAB" FEATURE**

A switch is provided on the control panel which causes the rear drive wheels to pivot to 28 degrees. A quick turn of the steering wheel to full left lock positions the front wheels at the same 28 degrees. This allows the TBG134 to "crab" sideways while backing up and remain parallel to the previously cut grooves. The TBG134 can thus groove in a 12' wide lane and realign for the next pass in one backward movement.

NO MACHINE ON THE MARKET TODAY OFFERS THIS FEATURE.

1/2





• Part Number: No

Number of Axles: 2 Straight Axles, 4 tires.

Distance between Axles: Approximately 8 feet

2/2